

2D Desktop Scanner

DP936



Features:

- Adjustable scanning head, suitable for various scenarios
- Automatic sensing and automatic scanning
- Scan code light and buzzer prompts
- Plug and play, no design required
- SHIGH-strength material, shock-proof and fall-proof



1D/2D



CMOS Image



USB



Restaurant



Plug&play



Cable 1.5m



RS232



Retail

Performance Parameters

Sensor Pixels	640 x 480 pixels (H)(V)
Decoding Ability	1D: Codabar, Code39, Code32, Pharmaceutical (PARAF), Interleaved 2 of 5, NEC 2 of 5, Code 93, Straight 2 of 5 Industrial, Code128, Straight 2 of 5 IATA, Matrix 2 of 5, Code 11, GS1-128, UPC-A, UPC-E, EAN/JAN-8, MSI, EAN/JAN-13, GS1 DataBar Omnidirectional, GS1 DataBar Limited, GS1 DataBar Expanded, China Post(Hong Kong 2 of 5), Korea Post. 2D: PDF417, Micro PDF417, GS1 Composite Codes, QR Code, Data Matrix, MaxiCode, Aztec, HANXIN.
Scan Range	0-160mm(EAN 13 13mil 90%PCS)
Motion Tolerance	4meters/second
Scan Mode	Automatic Induction Scanning
Field of view	44°(H) , 34°(V)
Print Contrast	20%
Scan Mode	Turn±360°,Elevation±65°,Declination±65°
Interface	USB(Drive-Free), USB-COM, RS232

Physical Parameters

Dimension	80mm*75mm*135.5mm
Material	ABM+PC
Cable Length	1.5M

Environmental Parameters

Operating Temperature	-20°C~60°C
Storage Temperature	-30°C~70°C
Ambient light	0~100000LUX
Relative Humidity	5%~95%RH(Non-condensing)
DropShock Resistance	Withstands multiple 1.5 meters drops to concrete

Electrical Parameters

Working Voltage	DC 5V±5%
Current	Standby current 190mA; Working current 240mA.